

# SDC075

## AI Tracking PTZ Camera



### Overview

SDC075 AI Tracking PTZ camera has perfect functions, superior performance, and rich video output interfaces including USB, HDMI, SDI and LAN. It offers vivid and high-resolution videos with a strong sense of depth and fantastic colour rendition. It supports H.264/H.265 encoding which makes motion video more fluent and clearer under low bandwidth conditions.

SDC075 AI Tracking PTZ camera is featured with advanced ISP algorithms and built-in high-speed processor, which allows it to track and detect presenter accurately and quickly. It fully satisfies demands by video conferencing, webcasting, Lecture capture, Tele-training, and Security, making it ideal for scenarios such as broadcast of teaching and remote meeting.

### Key Features

- High quality 1/2.8" CMOS sensor
- Support full HD resolution
- Leading Auto Focus Technology
- Support multi output formats (USB, HDMI, SDI, LAN)
- Multiple Audio/Video Compression Standards
- Support USB3.0 Dual Coding Stream
- Built-in Gravity Sensor
- Support multiple control protocols (VISCA, PELCO-D, PELCO-P)
- Support multiple control interfaces (RS232, RS485)
- Support various remote controls
- Quiet and smooth PTZ movement
- Support AI Human Detection
- Support audio input
- Support PoE

Sensor	1/2.8-inch high-quality CMOS sensor
Effective Pixels	16: 9 aspect, 2.07 megapixel
Resolution	Up to 1920 x 1080 at 60 fps
Optical Zoom	20x optical zoom
Digital Zoom	15x
Pan Rotation	±170°
Tilt Rotation	-30°~+90°
Pan Control Speed	0.1 -100°/sec
Tilt Control Speed	0.1-45°/sec
Preset Speed	Pan: 100°/sec, Tilt: 45°/sec
Preset Number	255 presets (10 presets by remote controller)
Focus	Auto/Manual
Aperture	Auto/Manual
Electronic Shutter	Auto/Manual
Camera Control	Network: VISCA over IP/ONVIF/RTMP/SRT Serial Port: VISCA/Pelco-P/Pelco-D
Audio input Interface	Dual channel 3.5mm linear input
External Power Supply	DC12V/2.5A
Warranty	2 years
Operating Temperature Range	-10~50 degrees centigrade
Operating Humidity Range	20%-80%
Storage Temperature Range	-10~70 degrees centigrade
Storage Humidity Range	20%~95%
Dimension	181mmX115mmX149mm
Weight	1.15KG

### Models and Scales

Models	Optical Zoom	Digital Zoom	Video Interface	NDI	PoE
SDC075-B20	20x	15x	SDI, USB3.0, HDMI, LAN	No	Yes
SDC075-B20N	20x	15x	SDI, USB3.0, HDMI, LAN	Yes	Yes

### Applications



Command & Control Centre



Conference Room



Education